

OPC
Range



17-01-25

MODEL	Working Pressure bar	Capacity m³/min FAD	Capacity m³/h FAD	Capacity cfm FAD	Installed Power kW	Speed rpm
3,6-4 bar compressors - 1 stage / 2 cylinders						
OPC 160-3,6	3,6	35,8	2148	1264	160	385
OPC 200-3,6	3,6	43,2	2592	1526	200	465
OPC 160-4	4	35,2	2112	1243	160	380
OPC 200-4	4	43,0	2580	1519	200	465
OPC 220-4	4	47,2	2832	1667	220	510
8 bar compressors - 2 stages / 2 cylinders						
OPC 45-8	8	7,7	462	272	45	445
OPC 55-8	8	9,5	570	335	55	530
OPC 75-8	8	12,5	750	441	75	700
OPC 75b-8	8	13,8	825	486	75	445
OPC 90-8	8	16,5	990	583	90	535
OPC 110-8	8	20,0	1200	706	110	640
OPC 132-8	8	23,0	1380	812	132	750
OPC 160-8	8	26,7	1600	942	160	425
OPC 200-8	8	30,4	1825	1074	200	505
OPC 250-8	8	42,5	2550	1501	250	400
OPC 280-8	8	47,1	2825	1663	280	450
OPC 315-8	8	53,0	3180	1872	315	520
OPC 355-8	8	58,0	3480	2048	355	470
10 bar compressors - 2 stages / 2 cylinders						
OPC 45-10	10	7,0	420	247	45	400
OPC 55-10	10	8,7	520	306	55	490
OPC 75-10	10	11,7	700	412	75	655
OPC 75b-10	10	12,5	750	441	75	400
OPC 90-10	10	15,0	900	530	90	485
OPC 110-10	10	18,0	1080	636	110	600
OPC 132-10	10	21,5	1290	759	132	690
OPC 160-10	10	24,2	1450	853	160	400
OPC 200-10	10	29,5	1770	1042	200	500
OPC 250-10	10	38,5	2310	1360	250	375
OPC 280-10	10	42,7	2560	1507	280	415
OPC 315-10	10	48,0	2880	1695	315	470
OPC 355-10	10	54,0	3240	1907	355	440
12-15 bar compressors - 2 stages / 2 cylinders						
OPC 45-13	13	5,7	342	201	45	340
OPC 55-13	13	7,2	432	254	55	430
OPC 75-13	13	9,8	588	346	75	575
OPC 90-12*	12	11,6	696	410	90	600
OPC 90-14*	14	11,3	678	399	90	600
OPC 110-14*	14	13,5	810	477	110	720
OPC 132-15*	13	16,5	990	583	132	450
OPC 132-15*	15	16,2	972	572	132	440
OPC 160-15	13	19,0	1140	671	160	450
OPC 160-15	15	17,0	1020	600	160	390
OPC 200-15	13	22,9	1374	809	200	530
OPC 200-15	15	21,8	1308	770	200	500
OPC 280-13*	13	38,4	2304	1356	280	390
OPC 315-13*	13	43,3	2598	1529	315	440
OPC 355-13*	13	49,2	2950	1736	355	500
16 bar compressors - 2 stages / 2 cylinders						
M3-10	10	3,1	186	109	30	765
M3-16	16	2,8	168	99	30	765

* previous model

Capacities according to ISO 1217

Above performances are subject to changes and can be adapted to specific requests

Technical modifications without prior notice.

ISO 1217

