



AF COMPRESSORS

OIL FREE PISTON AIR COMPRESSORS

PET
Range


17-01-25

MODEL	Capacity m³/h FAD		Capacity CFM		Installed power kW	Speed rpm	
	35 bar	40 bar	35 bar	40 bar		35 bar	40 bar
M 2 XS	120	120	71	71	30	450	450
M 2 S	180	180	106	106	37	550	550
M 2 A	215	215	127	127	45	660	660
CE 24 XS	315	315	185	185	55	340	340
CE 24 S	425	425	250	250	75	455	455
CE 24 A	510	490	300	288	90	535	510
L 3 XS	525	525	309	309	90	510	510
CE 24 B	600	600	353	353	110	640	640
L 3 S	640	640	377	377	110	625	625
CE 24 C	700	670	412	394	132	755	725
L 3 A	770	770	453	453	132	755	755
L 4 A	975	955	574	562	160	435	415
L 4 B	1100	1075	647	633	185	490	470
CE 46 A	1160	1120	683	659	200	520	510
L 5 XS	1260	1200	742	706	200	445	430
L 5 S	1330	1270	783	748	220	485	450
CE 46 C	1450	1425	853	839	250	525	505
L 5 A	1530	1500	901	883	250	465	460
L 5 B	1680	1630	989	959	280	510	505
L 6	1760	1730	1036	1018	280	390	370
L 6 A	1940	1910	1142	1124	315	425	415
CE 68 A	2100	2060	1236	1212	355	480	470
L 6 B	2170	2130	1277	1254	355	475	465
L 7	2330	2330	1371	1371	400	525	525
L 8 A	2500	2430	1471	1430	400	390	375
CE 68 B	2600	2570	1530	1513	450	510	500
L 8 B	2800	2735	1648	1610	450	440	425
L 9 A	3100	3030	1825	1783	500	485	475
L 9 B	3300	3230	1942	1901	550	520	500

Capacities according to ISO 1217

Above performances are subject to changes and can be adapted to specific requests

Technical modifications without prior notice.

ISO1217

www.afcompressors.com